

M39LTURNTABLE LADDER TECHNICAL DATA

CONCEPT

/ Working height 39 m

/ Rescue cage RC300 for 3 persons / 300 kg / Chassis Appropriate two-axle chassis,

16 - 18 t class

Ladder set 5-sections

STANDARD EQUIPMENT

/ VARIO jacking system

/ Large-volume equipment locker and podium set-up

/ Generous LED interior lighting

/ Ergonomic main control stand

/ Colour display on main control stand, easily swivelling into working position

I The angle of seat inclination is automatically set depending on the ladder angle which increases ergonomics and usability

/ 5-section ladder set with Magirus CS (Computer Stabilization)

/ Water piping with a capacity of up to 2,500 I/min

/ Rescue cage for 3 persons / 300 kg with central control stand and practical entry doors in front cagecorners

Increased safety at the scene by powerful LED lighting

/ Display indicators and computer monitoring for easy and safe operating

OPTIONALLY AVAILABLE

/ Also available as low profile chassis with a compact total vehicle height of approx. 3.100 mm

I Further suitable models of the Magirus rescue cage series:

- RC400-C "Compact" for 4 persons / 400 kg
- RC400 for 4 persons / 400 kg
- RC500 for 5 persons / 500 kg

/ Manually or electrically controlled water monitor, mountable or permanently integrated

/ Thermal imaging / real imaging camera at cage

/ Power supply to cage and various types of illumination

/ Pressure ventilator support at cage

/ Stretcher support: 200 kg / 270 kg

/ Load eye for load transport:

- Load eye on cage floor RC300: 300 kg
- Load eye on cage floor RC400-C / RC400: 400 kg / RC500: 500 kg $\,$
- · Load eye on top ladder section: 500 kg
- Load eye on lower ladder section: 4,000 kg

/ Magirus Safety Peak: anchor point for securing and rescuing up to 2 persons,

EN 795-certified

/ Functional equipment for rope rescuing and safety

/ Autopilot memory control, shaft rescue function, automatic ladder rest position

/ Remote diagnostic system

/ Variable custom designs and paint options

/ Magirus Rescue Loader RL500 to rescue obese people

/ Magirus FlexiFoam adapter

/ Wide range of additional equipment and options available



Ergonomic main control stand



RC300 for 3 persons / 300 kg



VARIO jacking system

Illustrations may include additional options. We reserve the right to make technical changes or improvements at any time without prior notice. Errors and omissions excepted.

MAGIRUS GmbH • Graf-Arco-Straße 30 • 89079 Ulm • Germany www.magirusgroup.com • magirus@cnhind.com